

INDUSTRIAL WHITE SOLUBLE (Maximum 0.2% NaCl)
MURIATE OF POTASH

Grade Code: F215

TYPICAL CHEMICAL ANALYSIS

Component/Equivalent	Symbol	Unit	Typical	Guaranteed
Potassium Chloride	KCl	%	99.75	
Potassium Oxide	K ₂ O	%	63.00	62.95 Minimum
Sodium Chloride	NaCl	%	0.10 - 0.20	0.2 Maximum
Moisture	H ₂ O	%	0.05	
Bromide	Br ⁻	ppm	50 - 150	
Calcium	Ca	ppm	10 - 30	
Chloride	Cl ⁻	%	47.53	
Lead	Pb	ppm	<1.0	
Magnesium	Mg	ppm	5 - 15	
Potassium	K	%	52.30	
Sodium	Na	%	0.04 - 0.08	
Sulfate	SO ₄	ppm	20 - 70	
Water Insolubles		ppm	30 - 70	

REAGENTS

Reagent	Unit	Typical	Range
Anticake Amine	ppm	200	150 - 250
De - dust oil	ppm	nil	

PARTICLE SIZE DISTRIBUTION

	Tyler Mesh	US Mesh	mm Mesh	Typical Cumulative %	Typical Range %
Retained on . . .	28	30	0.600	1.0	0 - 5
	35	40	0.425	17.0	10 - 35
	48	50	0.300	53.0	35 - 75
	65	70	0.212	80.0	65 - 95
	100	100	0.150	93.0	80 - 100
	150	140	0.106	98.0	90 - 100
Passing through	150	140	0.106	2.0	0 - 10

PHYSICAL PROPERTIES

Parameter	Unit	Typical/Range
Bulk density	lb/cu ft	70
	kg/m ³	1122
Angle of repose	degrees	29
Specific gravity	g/cm ³	1.94
Appearance		White fine and highly purified

Typical results are based on product expectations at load port.

< signifies "less than" the stated detection limit.

To the best of Canpotex's knowledge and belief, the information contained herein is accurate and reliable. The analysis values listed as 'Typical' in the above specifications are average values compiled from composite sample analysis and should not be considered a guaranteed specification, unless otherwise noted.

Revised March 2018